



TT 170 / TT 90



- TT 170 için Ø76, Ø90, Ø114 standart tambur
Ø76, Ø90, Ø114 rolls standard for TT 170



TT 170



TT 90

TEKNİK ÖZELLİKLER VE STANDART DONANIM

- İşleme tamburu sayesinde boru ve profil çapına göre uygun ağız açabilme
- Hareketli mengene sayesinde çabuk sıkma ve sökübilme
- Mengene sağ - sol ve ileri - geri hareket özelliği (Rulmanlı sistem)
- Dönerli mengene sayesinde 50°ye kadar açılı ağız açabilme
- Sürücü ile ayarlanabilir hız kontrolü
- 3" boruya kadar kaynak ağızı açabilme (TT 90)
- 6" boruya kadar kaynak ağızı açabilme (TT 170)
- Opsiyonel pnömatik mengene

TECHNICAL SPECIFICATIONS AND STANDARD ACCESSORIES

- Ability to open suitable dovetails according to the diameter of the pipe and profile with the help of processing drum
- Ability to tighten and loosen the parts quickly as a result of moving clamp
- Ability of clamp to move right and left sideways
- With movable clamp, notching up to 50° degrees angle
- Adjustable speed with inverter
- Notching operation up to 3" pipe (TT 90)
- Notching operation up to 6" pipe (TT 170)
- Optional pneumatic vice



TT 76



- TT 76 ve TT 90 için Ø19, Ø21, Ø25, Ø32, Ø38, Ø42, Ø48, Ø52, Ø60, Ø76 standart tambur
Ø19, Ø21, Ø25, Ø32, Ø38, Ø42, Ø48, Ø52, Ø60, Ø76 rolls standard for TT 76 and TT 90

TEKNİK ÖZELLİKLER VE STANDART DONANIM

- Metal boru ve profiller için uygun ağız açma
- Erişimi kolay üst kapak ile taşlama
- 1/2" den 2 1/2" e kadar kaynak ağızı açabilme
- 30° - 90° için hızlı taşlama ayarı
- Kolay ve hızlı değiştirilebilir bant zimpara
- Titreşim azaltma standı

TECHNICAL SPECIFICATIONS AND STANDARD ACCESSORIES

- Appropriate for notching operation of metal pipes and profiles
- Grinding with easy-to-access top cover
- Notching operation from 1/2" to 2 1/2" pipes
- Quick adjustment for grinding angle 30° - 90°
- Easy and fast change of abrasive belt
- Vibration reduced stand



TT 76



MODEL	TT 76	TT 90	TT 170
Mengene kapasitesi	Clamp capacity	Ømm	16-76
Ağız açma kapasitesi	Notching capacity	Ømm	16-76
Zimpara ölçüsü	Belt size	mm	100x2000
Motor gücü	Motor power	kW/V	2,2/380
Uzunluk	Lenght	mm	1250
Genişlik	Width	mm	700
Yükseklik	Height	mm	1150
Ağırlık	Weight	kg	170
			180
			250